

# Installation Instructions

## Castle Climber

Part # SC031



591 South Boulevard Street  
Gunnison, Colorado 81230  
info@idsculpture.com  
970-641-1747

### Specifications: Castle Climber

- Material: GFRC Concrete with Structural Foam
- Approximate uninstalled Size: 13'-9" x 7'-10" x 8'-0" Tall
- Approximate Weight: 5700 Lbs
- Maximum fall height: 7'-0" (with 1' of protective surfacing)
- Age group: 5-12 years old

### Required Parts (included):


- Castle Climber GFRC sculpture
- 1" lifting studs: 2ct
- 5/8" X 8 1/2" SS Wedge Anchor: 8ct
- Pick point plugs: 2ct
- Epoxy cup
- "Castle Climber" drawing set

### Recommended Equipment (not included):


- Hammer Drill
- 5/8"x 10" concrete drill bit
- Air compressor
- Hammer
- 15/16" Wrench
- 6' lifting straps: 2ct
- Large adjustable crescent wrench
- 16" Min. socket extension
- 15/16" Socket and ratchet
- Lift: Reach Type Forklift 8000lb Capacity or Crane
- 12' Spreader Bar

### Important Notes:

- *Warning: Installation over a hard surface such as asphalt, or packed earth may result in serious injury or death from falls.*
- *It is the responsibility of the installer to ensure all components are installed in compliance with ASTM F-1487.*
- *All site built footings should be allowed to cure for a minimum of 48 hours prior to installation.*



Typical Wedge Anchor Installation



Section

# Installation Instructions

## Castle Climber

### Part # SC031





591 South Boulevard Street  
Gunnison, Colorado 81230  
info@idsculpture.com  
970-641-1747

## PRE-INSTALL CHECKLIST

Please review prior to ordering and installing ID Sculpture products.

- ☐ 1. Verify that you have the recommended lifting equipment to unload and install your component, as specified by the installation instructions. Please check the installation instructions for the weight of each component and shipping dimensions.
- ☐ 2. Develop a proper plan to access the site and control access prior to opening.
- ☐ 3. Call your local utilities to locate any potential existing below grade equipment?
- ☐ 4. FOR ALL SCULPTURES: Verify you have accounted for adjustments to the footing depth based on your choice of safety surfacing material. Footing depth must be adjusted to compensate for the depth/thickness requirements of the selected safety surfacing (*see diagrams below*). Layout drawings show the uninstalled dimensions of the component. If you require a modification to a standard component, please notify ID Sculpture when placing your order. *Additional charges may apply.*



\*Critical Fall Height (CFH)

- ☐ 5. Verify that you have installed any required footings prior to the arrival of your sculptures. Please note, footings should be allowed to cure for a minimum of 7 days.

### Important Safety Note:

Please install and maintain adequate protective surfacing under and around your equipment. Never let children play on the equipment before protective surfacing is installed. Please consult ASTM F1487 for more information.

# Installation Instructions

## Castle Climber

Part # SC031




**ID SCULPTURE**

PLAY. CLIMB. EXPLORE.

### Sculpture Installation:

1. Locate and construct the footer based on the provided layout plan drawing.
2. Make sure that the Lifting Studs are securely threaded.
3. Attach the lift to the Lifting Studs located on the top of the piece using the (2) 6' lifting straps. Refer to rigging diagram (P.3).
4. Lift the sculpture using an appropriate reach forklift or crane taking care to equalize the load on straps.
5. Set the sculpture in place on the footing. Verify all use zones as defined by ASTM 1487 before drilling anchor holes.
6. **\*\*\*IMPORTANT!!!** Once the sculpture is placed on the footing, you must remove the 3"x3" Angle Iron shipping brace from sculpture frame with 15/16" socket and socket extension.\*\*\*
7. Drill through the holes in the mounting brackets with a 5/8"x10" hammer drill bit to a minimum depth of 7 1/2", clean holes with compressed air and brush.
8. Install the stainless steel wedge anchors and tighten.
9. Remove the Lifting Studs and install the Pick Point Plugs using the epoxy included.
10. Install resilient surfacing material in accordance with layout guidelines, and ASTM standards.

591 South Boulevard Street  
Gunnison, Colorado 81230  
info@idsculpture.com  
970-641-1747



Plan


# Installation Instructions

## Castle Climber


Part # SC031



591 South Boulevard Street  
Gunnison, Colorado 81230  
info@idsculpture.com  
970-641-1747



Rigging Section



Rigging Plan