

# Installation Instructions

## Chroma Climber

Part # SCo26



591 South Boulevard Street  
Gunnison, Colorado 81230  
info@idsculpture.com  
970-641-1747



## Specifications: Chroma Climber

- Material: GFRC Concrete with Structural Foam
- Approximate uninstalled Size: 6'-7" x 5'-0" x 7'-9" Tall
- Approximate Weight: 5000 Lbs
- Maximum fall height: 6'-0" (assumes 12" safety surfacing)
- Age group: 5-12 years old

## Required Parts (included):


- Chroma Climber
- "Chroma Climber" drawing set
- Bolt Hanger (lifting eye - fixi): 4ct

## Recommended Equipment (not included):


- 10' lifting straps: 4ct
- 1/2" quick link: 4ct
- Large adjustable crescent wrench
- Lift: Reach Type Forklift 6000lb Capacity or Crane

## Important Notes:

- *Warning: Installation over a hard surface such as asphalt, or packed earth may result in serious injury or death from falls.*
- *It is the responsibility of the installer to ensure all components are installed in compliance with ASTM F-1487.*
- *All site built footings should be allowed to cure for a minimum of 48 hours prior to installation.*



Typical Wedge Anchor Installation



Note:

When determining critical fall height please allow for +/- 2" tolerance in concrete surface

Section

# Installation Instructions

## Chroma Climber

Part # SCo26



591 South Boulevard Street  
Gunnison, Colorado 81230  
info@idsculpture.com  
970-641-1747

### Sculpture Installation:

1. Excavate subgrade as per drawing.
2. Secure the (4) 10' lifting straps to the pre-installed lifting points.
3. Lift the sculpture using an appropriate reach forklift or crane taking care to equalize the load on straps.
4. Place the sculpture and verify layout and all use zones as required by ASTM 1487.
5. Backfill and install resilient surfacing material in accordance with layout guidelines, and ASTM standards.

